

Avision | AV332U-RU Sheetfed Scanner



A Compact and Affordable Duplex Scanner





236"

Long











Features:

- AV332U scans 32 ppm/ 64 ipm at (A4, Color, 200 dpi)
- AV332U scans 32 ppm/ 64 ipm at (A4, Color, 300 dpi)
- Easy to carry due to the slim design
- Support embossed plastic cards
- Professional bundled software applications include Avision Button Manager V2, AVScan X, PaperPort SE 14
- Earth-friendly LED technology
- Compact ADF holds up to 50 pages
- Press and scan to cloud servers such as Google Drive, FTP, Evernote, and Microsoft SharePoint via Button Manager V2

Overview

The AV332U-RU is a 32ppm/ 64ipm, duplex sheetfed scanner that is fast, reliable, and affordable for business where scanning plastic ID cards, business cards, documents or other heavy card stock is necessary. With the straight paper path, the scanner supports paper from 27~413 g/m²(7 ~ 110 lb) in weight and in 8.5 x 14 in. (legal) in size and allow embossed plastic cards such as credit cards, or driver's license up to 1.25 mm thick to be transmitted smoothly. Ultrasonic multi-feed detection assures you that not a single page of your documents will be lost.

High Resolution of 1200 dpi

With a high resolution of 1200 dpi and advanced image processing technology, you can be assured documents can be converted in the highest image quality. In addition, with the build-in CIS (Contact Image Sensor) module, the AV332U-RU does not require any warm-up time.

Innovative Design to Save Your Space


The AV332U-RU boasts a unique and stylish design as both the input and output paper tray can be folded when not in use. The paper tray also helps to protect the unit from dust. Unlike bulky conventional scanners, the slim AV332U-RU can be easily carried and fit on a desk without taking up a lot of space.

Compact and earth-friendly design

The AV332U-RU is compact and earth-friendly in design since it uses CIS (contact image sensor) technology which requires smaller space and the LED lamp as the light source. The LED lamps are lower power consumption and are designed to last for the life of the scanner.

Ultrasonic Multi-Feed Detection

With the built-in ultrasonic multi-feed detection capability, the scanner allows you to set overlapped paper by detecting paper thickness between document. When multi-feed is detected a warning message will be prompted.



What We Have Bundled

The AV332U-RU comes with TWAIN and ISIS drivers, and are bundled with a suite of powerful software applications that include Avision Button Manager V2, AVScan X and Nuance PaperPort SE 14.

Avision | AV332U-RU Sheetfed Scanner

Avision's Button Manager V2 -Completes your scan with a single step



The Button Manager V2 main screen

Button Manager V2 makes it easy for you to scan and send your image to your favorite destinations with a press one button. Now the new version comes with an innovative feature to let you scan and automatically upload the scanned document to popular cloud repositories such as Google Docs, Microsoft SharePoint, or FTP. In addition, the iScan feature allows you to insert the scanned image or recognized text after optional OCR (Optical Character Recognition) process to your text editor such as Microsoft Word to get your job done easily and quickly.

AVScan X

-The Intelligent Document Management Tool



The AVScan X main screen

Document Imaging is the very first step of Document Management. However, poor quality images can cause serious problems to later indexing or storing processes. It may increase scanning labor costs and lowers the OCR accuracy. AVScan X ensures all documents are checked and polished at the time they are scanned such that the image quality is guaranteed before they are ready to use for other purposes.

AVScan X is an intelligent scanning and electronic filing solution. AVScan X possesses distinct features that convert and index scanned information into electronic documents for easy storage and fast retrieval.

Nuance PaperPort SE14

- The Professional Choice to Organize and **Share Your Documents**



PaperPort SE 14 is Nuance's most popular scanning and document management solution, carefully designed specifically for home office use. Part traditional file cabinet, part digital-document desktop, PaperPort SE 14 is the fastest and easiest way to scan, share, search and organize your documents. Additionally, PaperPort SE 14 now delivers anytime-anywhere access to your most important files however it's convenient for you using a PC, Mac, iPhone, iPad, or Android device.



Avision AV332U-RU Product Specifications

70151011703520110110		-
Paper Feeding:	ADF 50-page capacity	-
Scanning Technology:	Contact Image Sensor (CIS)	-
Light Sourcce:	LED	_
ID card thickness:	Up to 1.25 mm	_
Long Page Mode:	200 dpi: 6000 mm (236 in.)	× -
	300 dpi: 5540 mm (218 in.)	tion i to the
	600 dpi: 1500 mm (59 in.)	We have endeword to ensure that the information in this manual is accurate and that Avision is not responsible for printing or typographical errors. The above configuration for refere endeword to ensure that the information in this manual is accurate and that Avision is not responsible for printing or typographical errors. The above configuration for refere comb, the actual configuration (software, bardware) should be complied with the specification described in the purchase agreement wiskoin it. covers the indirectual property fully for the product outbods and design and the product outbod and design and the product outbod and design are subject to charge Avison reserves the right to the variance of the actual property fully of the product outbods and design and the product outbod and design are subject to charge Avison reserves the right to the
Scanning Size:	Max. 216 x 356 mm (Legal) (8.5 x 14 in)	e conf
	Min. 52 x 74 mm (2.0 x 2.9 in)	above
Scanning Speed:	32 PPM/ 64 IPM (BW, A4, 300 dpi)	. The
	32 PPM/ 64 IPM (color, A4, 200 dpi)	errors nt. . Avis
	32 PPM/ 64 IPM (color, A4, 300 dpi)	hical eeme iange
Paper Thickness:	27~413 g/m ² (7 ~ 110 lb)	ograp se agi
Resolution:	1200 dpi	rtypi urcha: ubject
Output Resolution:	75, 100, 150, 200, 300, 400, 600 and 1200 dpi	We have endeavored to ensure that the information in this manual is accurate and that Aviaton is not responsible for printing or typographical errors. The above configuration is for reference only the acturation for the area handware is houd be completed with the protocol and the approximation is a works the indexcutal property that of the protocol design and the product outdock and design are subject to change. Aviation the tright to the advison in covers the indexcutal property that of the product addock and design are subject to change. Aviation reserves the right to the advison in covers the indexcutal property that of the product addock and the product outdock and design are subject to change. Aviation reserves the right to the advisor in covers the indext of product addock and design and the product outdock and design are subject to change.
Halftone Patterns:	Dither and Error Diffusion	r prin ed in 1 esign
Grayscale mode:	16-bit input 8-bit output	ble fo scribind de
Color mode:	48-bit input 24-bit output	ponsi on de look i
File Formats:	BMP, PNG, GIF, JPEG, PDF, Searchable PDF	otres ificati ct out
	Multi-Page TIFF, TIFF, RTF, TXT, XPS,	n is n spec
	DOC, XLS, PPT, DOCX, XLSX, PPTX, HTML.	Avisio th the the p
Bundled Software:	Avision Button Manager V2, Avision AVScan X	that / ed wi
	Nuance PaperPort SE 14	e and ompli desig
Interface/Drivers:	USB 2.0 / TWAIN , ISIS , WIA	curate lbe condi-
Power Supply:	Input: 100~240 VAC, 50/60 Hz	l is ac hould
	Output: 24V, 1.5A	anua are)s uct ou
Power Consumption:	Operation: 15W Sleep: 1.6 W	. his m ardw. prodi
	Ready: 6W Off: 0.27W	on in . are, h
Environmental Factors:	Operating temperature: 10°C to 35°C (50°F to 95°F)	mati softw
	Operating humidity: 10% to 85%	e info tion (erty ri
Acoustic Noise:	Standby: <25 dB Operating: <55 dB	figura prope
Maximum (WxDxH):	282 x 457 x 334 mm	ure the lcon
Minimum (WxDxH):	282 x 152 x 165 mm	o ens actua
Weight:	2.4 kg	v.The theil
Recommended Daily	up to 5,000 Sheets	We have endewored to ensure that the information in this manual is accurate and that Avision is not responsible for printing or typographical error. The above configuration is or reference only the actual registration of toftware hardware) should be complete with the provide at the prover and the prover special and beached at the proversible for printing or typographical error. The above configuration is advison in covers the indirection provement and the product outlook and design as subject to change Avision reserves the right to the subject to change Avision reserves the right to the advisor and the product outlook and design as subject to change Avision reserves the right to the subject to change Avision reserves the right to the advisor and the product outlook and design as subject to change Avision reserves the right to the subject to change Avision reserves the right to the advisor and the product outlook and design as subject to change Avision reserves the right to the subject to change Avision reserves the right to the subject to change at the subject to the right to the subject to change at the right to the subject to change at the right to the subject to change at the right to the subject to the right at the right to the subject to the subject to change at the right to the subject to the right to the right to the subject to change at the right to the subject to the right to the right to the subject to the ri
Duty Cycle:		ve en erenc n Inc.
Multi-feed Detection:	Ultrasonic Sensor	Me ha orref

System Requirements

CPU: Intel Core i3 (2.1GHz) or Higher
Memory: 2GB (32ibit Windows)
4GB (64bit Windows)
DVD-ROM: DVD ROM Drive
USB: USB 2.0
Windows Operating System:
Windows 10, 8.x, 7, Vista, SP3, XP (32 & 64 bit
Contents
Scanner
Power Supply
Quick Guide
USB 2.0 Cable
CD-ROM includes:
-Scanner Driver
(TWAIN/ISIS Driver)
-Avision Button Manager V2
-Avision AVScan X
-Nuance PaperPort SE 14
· · · · · · · · · · · · · · · · · · ·



www.avision.com

Specifications subject to change without notice.

Avision Inc.|No. 20, Creation Rd. I, Hsinchu Science Park 300093, Taiwan, R.O.C. | Tel: 886-3-5782388 | Fax: 886-3-5777017 | sales@avision.com.tw Avision Europe GmbH | Siemensring 91 | 47877 Willich, Germany | Tel: +49-2154-88850-0 | Fax: +49-2154-88850-29 | w.kuo@avision-europe.com